

# IQ Digital Back range

## Technical Specifications

PHASEONE

what the world's best photography is made of

### IQ3



### IQ1



### IQ2



#### Specifications

	IQ3			IQ1			IQ2
	100MP	80MP	50MP	100MP	80MP	50MP	60MP Acromatic
<b>Resolution</b>	101 Megapixel	80 Megapixel	51 Megapixel	101 Megapixel	80 Megapixel	51 Megapixel	60 Megapixel
<b>Long exposure</b>	60 minutes	60 minutes	60 minutes	60 minutes	2 minutes	60 minutes	1 minutes
<b>16 bit Opticolor+</b>	yes	yes	n/a	yes	yes	n/a	n/a
<b>Dynamic range</b>	15 f-stops	13 f-stops	14 f-stops	15 f-stops	12.5 f-stops	14 f-stops	13 f-stops
<b>Sensitivity (ISO)</b>	50 - 12800	50 - 800	100 - 6400	50 - 12800	35 - 800	100 - 6400	200 - 3200
<b>Sensitivity (ISO) - Long Exp.</b>	50 - 12800	200 - 3200	100 - 6400	50 - 12800	n/a	100 - 6400	n/a
<b>Sensor+ (ISO) - 1/4 res.</b>	n/a	200 - 3200	n/a	n/a	140 - 3200	n/a	n/a
<b>Lens factor</b>	1	1	1,3	1	1	1,3	1
<b>Sensor type</b>	CMOS	CCD	CMOS	CMOS	CCD	CMOS	CCD
<b>Sensor Size</b>	53.7 x 40.4	53.7 x 40.4	44 x 33	53.7 x 40.4	53.7 x 40.4	44 x 33	53.7 x 40.3
<b>Active pixels</b>	11608 x 8708	10328 x 7760	8280 x 6208	11608 x 8708	10328 x 7760	8280 x 6208	8964 x 6716
<b>Pixel size (micron)</b>	4.6 x 4.6	5.2 x 5.2	5.3 x 5.3	4.6 x 4.6	5.2 x 5.2	5.3 x 5.3	6.0 x 6.0
<b>Output image dim. 300 DPI</b>	98.3 x 73.2 cm	87.4 x 65.6 cm	70.1 x 52.6 cm	98.3 x 73.2 cm	87.4 x 65.6 cm	70.1 x 52.6 cm	76.1 x 57 cm
<b>Output image dim. 600 DPI</b>	49.1 x 36.9 cm	43.7 x 32.8 cm	35.0 x 26.3 cm	49.1 x 36.9 cm	43.7 x 32.8 cm	35.0 x 26.3 cm	38 x 28.5 cm
<b>Mount options*</b>	XF, H	XF, H, V	XF	XF, H	P, H, V, C	P, H, V, C	P, H, V, C
<b>3.2" Touch Display</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>High Bandwidth Interface</b>	Yes	Yes	Yes	n/a	n/a	n/a	n/a
<b>XF Powershare</b>	Yes	Yes	Yes	n/a	n/a	n/a	n/a
<b>Wi-Fi 802.11 n</b>	Yes	Yes	Yes	n/a	n/a	n/a	Yes
<b>Captures per second</b>	14-bit	16-bit		14-bit	16-bit		
<b>Focal Plane (Full res.)</b>	1,4	0,7	0,8	1,4	0,7	0,8	1,8
<b>Focal Plane (Sensor+)</b>	n/a		1,1	n/a		1,1	n/a
<b>Leaf shutter (Full res.)</b>	1.2	0,7	0,7	1.2	0,7	0,7	1,4
<b>Leaf shutter (Sensor+)</b>	n/a		1	n/a		1	n/a

#### Images

IQ3 100MP © Alexia Sinclair IQ3 80MP © David LaChapelle IQ3 50MP © Anja Poulsen IQ1 100MP © Vincent Lions

#### Mount options\*

XF: XF, DF+ and DF  
P: DF+ and DF  
H: Hasselblad H1 and H2  
V: Hasselblad V-series  
C: Contax 645AF

# XF Camera System

## Feature Differentiation

### Sensor Choices

XF Camera System Feature Differences	XF IQ3 Camera System	XF IQ1 Camera System
CMOS Range	100MP 50MP	100MP 50MP
CCD Range	80MP	80MP
CCD Achromatic (IQ2)	60MP	

### Sensor Core Technology

	IQ3 100MP	IQ1 100MP
IIQ L 16 Bit	Yes	CMOS only
Long Exposure	Yes	No
HDMI	IQ3 100MP	No
Electronic Shutter (ES)	IQ3 100MP	No

### Tools & Features

	Yes	No
Capture from Live View	Yes	No
Exposure Calculator	Yes	No
XF Camera Controls from Home screen	Yes	Yes
XF Camera Controls from Tool view (inside play)	Yes	No
XF Camera Controls from Camera Menu	Yes	No
XF Camera Menu with settings for XF	Yes	No
Exposure Zone Tool	Yes	No
Clip Warning Tool	Yes	No
Auto ISO and ISO control	Yes	No

### Storage & Connectivity

	XF IQ3 Camera System	XF IQ1 Camera System
Integrated Wi-Fi	802.11n	No
USB 3	Yes	Yes
Firewire 800	Yes	Yes
Flash Sync port	Back and Prism	
High capacity back interface	Yes	No
Storage Media	UDMA 7, CF-card slot with spring loaded cover	
Secure Storage System	3S Technology	
Tripod socket	1/4 inch & 3/8 inch	
Storage Engine	1GB Image buffer	

### Power

	Yes	No
Power Share with hot pluggable batteries	Yes	No
Full system power via XF Power Supply	Yes	No
Advanced Battery Status indicators	Yes	No
USB3 Charging from Hub(1500mA)	Yes	No

### Flash

Flash trigger	Integrated Profoto Air Wireless
Wireless trigger range	20m (outside)
Back flash sync	Yes
Flash sync speed focal plane shutters (max)	1/125s
Flash sync speed leaf shutters (max)	1/1600s
Flash Remote Control	Profoto Air up to 6 groups

### Warranty

Warranty:	XF IQ3 Camera System	XF IQ1 Camera System
5 Year Warranty	Yes	No
5 Year Uptime Guarantee	Yes	No
Free lens choice upon purchase	Yes	No

### Packaging

	Yes	No
Pelican Sorm Case (Watercase with handle and wheels)	Yes	No
Modular F-stop ICU for camera system	Yes	No
Laptop compartment with Build in Sunshade (Tether station)	Yes	No
Card Reader and CF card	Yes	No
Lens Calibration plate	Yes	No
2 batteries	Yes	No
Tech camera sync cable	Yes	No

### Operating Requirements

Temperature	-10° to 50° C 14° to 122° F
Humidity	0 to 80 % (non-condensing)